



Tok

STEP UP & STAND OUT

Clear Digital™ presents Tok™, the adjustable podium that transforms your presentations with digital precision and practical versatility.

Effortless Adjustment: Height settings from 39.3" to 47.2"

Brilliant Display: 21.5" LED capacitive touchscreen

Responsive Control: Integrated Intel 8th gen CPU

Seamless Casting: Built-in wireless transmitter

Mobile Versatility: Wheeled base and 5-hour battery



Display

Size: 21.5"
Panel Type: IPS
Response Time: 17 ms
Aspect Ratio: 16:9
Display Area: 18.77" × 10.56"
Resolution: 1920 × 1080
Pixel Pitch: 0.24825 × 0.24825 mm
Refreshing Frequency: 60Hz

Color Depth: 16.7 M (8bit)
NTSC (Typ): 73%
Contrast Ratio: 1000:1
Viewing Angle: 178° (H/V)
Brightness with Glass (Typ): 250 cd/m²
Lifetime: ≥ 30,000 hours
Back Light Unit: ELED

Wireless Transmission

WIRELESS SCREEN
Wireless Transmission Transmitter: Built-in
Transmission Delay: Average delay < 133 ms
Operating Distance: <10 m
Operating Frequency: 2.4GHz/5GHz

WIFI
Wi-Fi Version: 802.11 a/b/g/n/ac
Operating Frequency: 2.4GHz/5GHz

Audio

MICROPHONE
Quantity: 2
Type: Gooseneck microphone
Pickup Distance: <7.8"
Sensitivity: -40dB ± 2dB
Frequency Range: 40Hz-16KHz
Sampling Rate: 32KHz

LOUDSPEAKER
Sound Channel: 2.0
Output Power: 2 × 2.5W

Display Interactivity

CAPACITANCE
Sensing Type: P-Cap + EMR
Touch Tool: Finger
Touch Point: 10 points touch
Response Time: < 15 ms
Minimum Object Size: 5 mm
Accuracy: 2 mm

ELECTROMAGNETIC
Touch Tool: Electromagnetic stylus
Touch Point: Single point touch
Accuracy: 0.5 mm
Writing Height: 10 mm ± 2 mm
Features: Finger/Stylus Recognition, Palm Rejection, Pressure Sensitivity

Built-In System

System Version: Windows 10
CPU: Intel 8th 8250U

RAM: 8GB
ROM: SSD 128GB

I/O Ports and Buttons

USB 2.0 (2), HDMI OUT (1), AUX OUT (1), MIC IN (2), DC IN (1)
 Buttons (4): Power, Control Column Up, Control Column Down, Microphone Mute

Power

Power Requirements: 100-240 V~50/60Hz 2.0 A
Overall Power: 200W
Standby Power: <0.5W

Battery: Lithium-ion 13000mAh;
 ~5 hours standard slide presentation

Control Parameters

Control Mode: Electric control
Lifting Speed: Up: 0.04 in/s; Down: 0.04 in/s

Lifting Distance: Min:39.3"; Max:47.2"

Physical Specifications

Dimension L×H×D: 31" × 15.7" × (39.3"~47.2")
Wheels: 2
Max Load: 11 lb
Net Weight: 72.9 lb

Gross Weight: 98.3 lb
 The intelligent podium can be separated from the lifting column and used separately.

Accessories

10' Power Cord (1), 10' HDMI cable (1), Stylus (1), Microphone (2), Wireless Module (1), Wireless Audio Module (1)

Environmental Conditions

Operation Temperature: 32°F - 104°F
Operation Humidity: 10% - 90% RH
Storage Temperature: -4°F - 140°F

Storage Humidity: 10% - 90% RH
Altitude: Below 16,000 ft